



SAFETY AT THE HIGHEST LEVEL
Ladder Stand off.
Assembly Instructions



USA

Kee Safety, Inc.
100 Stradtman Street
Buffalo, NY14206

Tel: (716) 896 4949
Fax: (716) 896 5696
Toll Free: (800) 851 5181
www.keesafety.com
Email: info@keesafety.com

Canada

Kee Safety, Ltd.
40 North Rivermede Rd., Units 6-7
Concord, Ontario L4K2H3

Tel: (905) 669 1494
Fax: (905) 669 4347
Toll Free: (877) 505 5003

PLEASE BE ADVISED: Before assembling the Ladder Stand off for the first time, it is highly recommended that Installers familiarize themselves with the component parts and carry out a test assembly and disassembly in a safe area away from the point of final installation. All component parts detailed in the operating instructions must be used in the assembly of the system. Should a piece be missing or appear defective do not continue to assemble and contact Kee Safety immediately.

Step 1



Ladder stand-off ready for attaching to the Ladder.

Step 2



Position the ladder stand-off over the top end of the ladder ensuring the hooks are pushed firmly over the rungs.

Step 3



Pull the spring hook over the second rung ensuring it's firmly secured into position. **WARNING!** It is very important this spring hook is fixed into position before use, as it prevents the Ladder stand-off sliding off the top end of the Ladder.

Step 4



FIG 1. Access Corners

Position the Ladder against the wall or to access corners **FIG 1.**

Step 5



Use Ladder spurs supplied by Easi-Dec to aid stability and prevent outward slip.

Remember

- Work carefully – Never rush.
- Always fit the spring hook.
- Do not use in adverse weather conditions.
- Always erect using the 4:1 rule.

Dismantle: Reverse the above procedure.